

S-Bt Smart Biotherm, Compact CO₂ Incubator



DESCRIPTION

S-Bt Smart Biotherm is designed for work in the areas of cell biology (operations with animal cell cultures and tissues), molecular biology (DNA/RNA reaction analysis, hybridization reactions), biotechnology (synthesis of target proteins and other molecules), immunology (synthesis of antibodies and other proteins of immune system).

Unit provides a six-sided heating: the heating elements are located on the walls and on the door, thus providing excellent uniform temperature distribution, regardless of external factors, such as ambient temperature and positioning of the device.

Built-in infrared CO₂-sensor allows accurate control of the CO₂ level. The sensor makes measurement non-sensitive to changes in temperature and humidity inside the incubator.

The chamber is made of stainless steel with smoothed seams to minimize contamination and to facilitate cleaning.

S-Bt is equipped with a UV air recirculation system - 1 UV lamp and a fan are mounted behind the rear wall, providing decontamination of the working volume.

A convenient access port is built in the wall of the incubator for easy output of wire sensors or devices' installed inside. The access port is heated independently to prevent formation of condensate.

Unit is equipped with error tracing and alarm systems, which significantly lower potential risks during operation.

Unit is equipped with a "black box" system that records temperature, humidity and CO₂ levels, as well as statuses for door opening, UV lamp, fan and errors, to the inner memory.

Bluetooth connection to PC is available.

SPECIFICATION

Working chamber material	Stainless Steel (1 mm)
Temperature setting range	+25°C ... +60°C
Temperature stability	±0.1°C
Temperature uniformity at +37°C	±0.3°C
Working volume	46 litres
Number of shelves	3 (max. 6)
Presence of the inner glass door	+
Relative humidity	>90% @ 37°C
Humidity delivery	Water Pan
CO ₂ control range	0 - 20%
CO ₂ sensor	Infrared CO ₂ sensor
Temperature and CO ₂ level input	Digital
UV lamp	1 × 6 W, TUV G6T5
Data output	Wireless



CAT. NR.

	S-Bt Smart Biotherm
BS-010425-A01	230VAC 50/60Hz Euro plug
BS-010425-A03	230VAC 50/60Hz UK plug
BS-010425-A02	230VAC 50/60Hz AU plug
-----	Optional accessories
BS-010425-AK	Shelf
BS-010425-BK	PC software and Bluetooth adapter
BS-010425-CK	Incubator stacking device
-----	Replacement parts
BS-010425-S01	Hydrophobic filter
BS-010425-S03	Access port seal

Biosan SIA., Ratsupites 7, build. 2, Riga, LV-1067, Latvia, Phone: +371 674 261 37, Fax: +371 674 281 01,
E-mail: marketing@biosan.lv, <http://www.biosan.lv>

S-Bt Smart Biotherm, Compact CO₂ Incubator



Access port	1 (ø 26 mm)
Dimensions	400 x 410 x 580 mm
Weight	37.7 kg
Nominal operating voltage	230B, 50/60 Hz; 115 V, 50/60 Hz