

UVR-Mi, UV Cleaner-Recirculator



DESCRIPTION

UVR-Mi is ideal for air disinfection in hospitals (especially in outpatient departments, operating rooms, emergency rooms, delivery rooms etc.), kindergartens, research laboratories, veterinary clinics.

The devices provide complete protection from direct ultraviolet radiation.

Advantages of **UVR-Mi**:

- **UVR-Mi** is the more powerful model of UV air flow cleaner with two UV-lamps
- Full user protection from direct UV radiation;
- Two operation modes — short time (under timer control) and continuous operation;
- Indication of UV lamps working hours.



Recirculators fixation:

- Convenient fixation on walls (standard)
- Mounting on a movable tripod (optional)

SPECIFICATION

| | |
|---|--|
| UV radiation source: | 2 lamps - 25W Bactericidal, TUV25WG13 UV-C |
| UV radiation level | 36 mW / cm ² / s |
| Air-flow productivity | 14 m ³ /hour |
| Full user protection from direct UV light | + |
| Display | LCD |
| UV lamp operation indicator | + |
| UV lamp lifetime counter | + |
| Timer | 1 min-24 hrs / non-stop |
| Automatic switch ON/OFF | + |
| Lamp fault detection | + |
| Overall dimensions (WxDxH) | 110 x 135 x 660 mm |
| Weight | 3.4 kg |
| Nominal operating voltage | 230 V, 50 Hz |
| Power consumption (230V / 120 V) | 110 W (0.5 A) |
| --- | --- |
| Tripod UVR-S dimensions | 600 x 600 x ~1100 mm |

CAT. NR.

| |
|--|
| UVR-Mi incl. power plug |
| BS-040110-AAA 230VAC 50/60Hz Euro plug |
| BS-040110-AAB 230VAC 50/60Hz UK plug |
| BS-040110-AA3 230VAC 50/60Hz AU plug |
| please, inquire 100VAC 50/60Hz US plug |
| please, inquire 120VAC 60Hz US plug |
| ----- Optional accessories |
| BS-040105-AK Tripod UVR-S |
| BS-040110-AK IQ OQ document |
| BS-040110-BK PQ document |