Biosan SIA, Ratsupites iela 7 k-2, Riga, Latvia, LV-1067 E-mail: marketing@biosan.lv, www.biosan.lv Phone:+37167426137

TS-DW, Thermo–Shaker for deep well plates

DESCRIPTION

TS-DW Thermo-Shaker is designed for shaking and incubating deep well plates.

A multisystem principle, used in the design of the Thermo-Shaker, allows operating it as 3 independent devices: Incubator, Plate shaker and Thermo–Shaker.

TS-DW provides excellent temperature uniformity across the plate due to patented two-sided heating of the block and the lid, contour heating of the block and close proximity of heating elements to plate walls.

There is a number of interchangeable blocks to suit different plates such as Eppendorf® 96/1000 μ l, Sarstedt® Megablock 96/2200 μ l, Porvair® 96/2000 μ l, Axygen® 96/2200 μ l. Also we can manufacture a customized block on request.

Deep Well Plate Thermo–Shaker provides:

- Soft or intensive sample shaking
- Rotation speed regulation, stabilization and indication
- Even rotation amplitude throughout the Thermo-Shaker platform
- Exceptional temperature uniformity across the plate
- Required operation time setting and indication
- Automatic stopping of the platform movement after expiration of the set time
- Setting and indication of the required temperature on the platform
- A variety of changeable blocks that can accommodate most popular deepwell plates
- Automatic fault diagnostics (temperature sensor, platform heating, lid heating etc.)

Application fields:

- Cytochemistry for in situ reactions
- Immunochemistry for immunofermentative reactions
- Biochemistry for enzyme and protein analysis
- Molecular biology for nucleic acid extraction

Separate blocks to accommodate different deepwell plates will be released. For example:

Deep Well Plates NUNC® 96/2000 µl Deep Well Eppendorf® 96/0.5 ml

The block for deepwell plate is mountable, thus a custom plate module can be manufactured on request

Temperature Calibration Function

With the help of the temperature calibration function the user can calibrate the unit approx. $\pm 6\%$ of the selected temperature to compensate differences in the thermal behaviour of plates from different manufacturers.



CAT. NUMBER

Without thermoblock	Without thermoblock
BS-010159-A02	230VAC 50/60Hz Euro plug
BS-010159-A03	230VAC 50/60Hz UK plug
BS-010159-A05	230VAC 50/60Hz AU plug
BS-010159-A04	100VAC 50/60Hz US plug, 120VAC 60Hz US plug
BS-010159-GK	IQ OQ document
BS-010159-HK	PQ document



Premium

SPECIFICATIONS

Temperature setting range	+25°C +100°C
Temperature control range	5°C above ambient +100°C
Temperature setting resolution	0.1°C
Temperature uniformity at +37°C	±0.1°C*
Temperature accuracy at +37°C	±0.5°C*
Time of platform heating from +25°C to +37°C	6 min*
* for B-2E thermoblock	-
Temperature calibration coefficient range	0.9361.063 (± 0.063)
Speed control range	250–1400 rpm
Digital time setting	1 min–96 hrs (1 min increment)
Timer sound signal	+
Orbit	2 mm
Display	LCD, 16 x 2 signs
Overall dimensions (W×D×H)	240 x 260 x 160 mm
Weight	5.1 kg
Input current/power consumption	12 V, 4.8 A / 58 W
External power supply	Input AC 100–240 V; 50/60 Hz; Output DC 12 V

ACCESSORIES

